

CLAIMS

1. (*CURRENTLY AMENDED*) A method for generating a reference transmission signal for use in testing a communications system, comprising:
 - capturing a data packet transmission signal containing a plurality of reference data;
 - digitizing said data packet transmission signal;
 - retrieving at least a selected portion of said plurality of reference data from said digitized data packet transmission signal to produce a plurality of retrieved data;
 - modulating a carrier signal with said plurality of retrieved data to produce a digital transmission signal; and
 - storing said digital transmission signal following said modulating of said carrier signal and prior to a use of said digital transmission signal in producing said reference transmission signal for transmission and ~~demodulation~~; demodulation;
 - retrieving said stored digital transmission signal; and
 - frequency up-converting said retrieved digital transmission signal to produce said reference transmission signal.
2. (*ORIGINAL*) The method of claim 1, wherein said capturing a data packet transmission signal containing a plurality of reference data comprises receiving said data packet transmission signal as an analog signal.
3. (*ORIGINAL*) The method of claim 1, wherein said capturing a data packet transmission signal containing a plurality of reference data comprises receiving said data packet transmission signal as a wireless signal.
4. (*ORIGINAL*) The method of claim 1, wherein said capturing a data packet transmission signal containing a plurality of reference data comprises receiving said data packet transmission signal as a wired signal.

AMENDMENT D

5. *(ORIGINAL)* The method of claim 1, wherein said retrieving at least a selected portion of said plurality of reference data from said digitized data packet transmission signal to produce a plurality of retrieved data comprises demodulating at least a selected portion of said digitized data packet transmission signal to produce a plurality of demodulated data.

6. *(ORIGINAL)* The method of claim 1, wherein said retrieving at least a selected portion of said plurality of reference data from said digitized data packet transmission signal to produce a plurality of retrieved data comprises decoding at least a selected portion of said digitized data packet transmission signal to produce a plurality of decoded data.

7. *(ORIGINAL)* The method of claim 1, wherein said modulating a carrier signal with said plurality of retrieved data to produce a digital transmission signal comprises encoding said carrier signal with said plurality of retrieved data.

8. *(ORIGINAL)* The method of claim 1, wherein said storing said digital transmission signal comprises storing said digital transmission signal in memory.

9. *(PREVIOUSLY PRESENTED)* The method of claim 1, further comprising modifying one or more selected bits of said plurality of retrieved data prior to said modulating a carrier signal with said plurality of retrieved data to produce said digital transmission signal.

10. *(CANCELED)*

11. *(CANCELED)*

12. *(CURRENTLY AMENDED)* An apparatus including circuitry for generating a reference transmission signal for use in testing a communications system, comprising:

signal capture means for capturing a data packet transmission signal containing a plurality of reference data;

digitizer means for digitizing said data packet transmission signal;

AMENDMENT D

first data retrieval means for retrieving at least a selected portion of said plurality of reference data from said digitized data packet transmission signal to produce a plurality of retrieved data;

signal modulator means for modulating a carrier signal with said plurality of retrieved data to produce a digital transmission signal; and

storage means for storing said digital transmission signal following said modulating of said carrier signal and prior to a use of said digital transmission signal in producing said reference transmission signal for transmission and ~~demodulation~~; demodulation;

second data retrieval means for retrieving said stored digital transmission signal; and
frequency conversion means for frequency up-converting said retrieved digital transmission signal to produce said reference transmission signal.

13. ~~(ORIGINAL)~~ The apparatus of claim 12, further comprising data modifier means for modifying one or more selected bits of said plurality of retrieved data prior to said modulation of a carrier signal with said plurality of retrieved data to produce a digital transmission signal.

14. ~~(CANCELED)~~

15. ~~(CANCELED)~~